

# MG21 Series

## Cloud-managed cellular gateway



### Overview

MG21 is a Meraki cellular gateway device. It will allow customers to use Meraki gear with cellular as a primary active uplink. MG21 only has a cellular connection as its uplink and acts as a wired uplink to devices that are attached to it (i.e., MX or any other router). MG21 can work with any routing device, Meraki or non-Meraki. With additional 802.3af compatibility, the MG can be placed anywhere and powered via power over ethernet (PoE) like any access point. This gives users the option for optimal physical placement for signal quality – a cornerstone for wireless WAN communications.

### MG series and Meraki cloud management: a powerful combo

All Meraki devices are managed via the Meraki cloud, with an intuitive browser-based interface. The MG series are self-configuring and managed over the web, and can be rapidly deployed at remote locations without any assistance from end-users.

Meraki Cloud services monitor all devices 24x7 and deliver real-time alerts if any devices encounters a problem. Remote diagnostics tools enable real-time troubleshooting through any web browser. New features and enhancements are delivered seamlessly over the web, so you never have to manually download software updates or worry about missing critical security vulnerability patches.

### Product highlights

- 2 GbE ports for routers in HA mode
- 1 802.3af compliant power over ethernet port to power the MG in challenging locations
- Local dashboard for easy initial device configuration
- Self-configuring, plug-and-play deployment
- Sleek, low profile design
- Built-in CAT 6 LTE connectivity
- IP67 rated for environments of all types

## Models: MG21-HW-NA, MG21-HW-WW

<b>Recommended use cases</b>	Wired uplink to MX or any third-party router
<b>Recommended downstream devices</b>	Up to 2 devices
<b>LAN Interfaces</b>	2
<b>PoE IN Port</b>	1 * 802.3af compatible
<b>Dimensions (w x d x h)</b>	160.45 x 160.45 x 34.45mm
<b>Weight (without accessories)</b>	487g
<b>Power supply</b>	12V/1A, 48-57V DC/0.35A
<b>Operating temperature</b>	4°F to 113°F (-20°C to 45°C)
<b>Humidity</b>	5% to 95% non-condensing

## Models: MG21E-HW-NA, MG21E-HW-WW

<b>Recommended use cases</b>	Wired uplink to MX
<b>Recommended downstream devices</b>	Up to 2 devices
<b>LAN Interfaces</b>	2
<b>PoE IN Port</b>	1 * 802.3af compatible
<b>Dimensions (w x d x h)</b>	165.7 x 160.45 x 34.45mm
<b>Weight (without accessories)</b>	489g
<b>Power supply</b>	12V/1A, 48-57V DC/0.35A
<b>Operating temperature</b>	4°F to 113°F (-20°C to 45°C)
<b>Humidity</b>	5% to 95% non-condensing

## Accessories

Antenna types: Dipole and patch  
Antenna gain (in dBi): 2.72dBi



# Features



## Self-configuring, cellular primary

If a certified carrier SIM card is inserted, the MG21 brings up the cellular connection and automatically connects to the Meraki cloud, downloads its configuration, and joins your network.

## Industry-leading cloud management

Meraki’s award-winning cloud management architecture unifies LAN and management under a web based dashboard, and scales easily from small deployments to large, multi-site deployments with tens of thousands of devices. The Meraki dashboard provides intuitive yet powerful role-based administration, firmware updates, configuration changes, email alerts, and easy to audit change logs.

## Local Status Page (LSP)



# MG21 specifications

## Performance

300 Mbps CAT 6 LTE integrated modem

## Interfaces

1 \* PoE IN

LAN interfaces: 1 x GbE

1 x CAT 6 LTE modem for cellular connectivity

## Monitoring and reporting

Throughput, connectivity monitoring

Org-level change logs for compliance and change management

## Environmental specifications

Power: 12V/1A, 48-57V DC/0.35A

Operating temperature: -22°F to 122°F (-30°C to 50°C)

Humidity: 5 to 95% non-condensing

Desktop or wall mount or ceiling mount  
(all standard mounting hardware included)

## Remote diagnostics

Live remote packet capture

Real-time diagnostic and troubleshooting tools

## Management

Managed via the web using the Meraki Cloud Controller

Single pane of glass management of wired and wireless networks

Zero-touch remote deployment (no staging needed)

Automatic firmware upgrades and security patches

Centralized policy management

Org-level two-factor authentication and single sign-on

Role based administration with change logging and alerts

## Integrated cellular

LTE bands: (North America) 2,4,5,12,13,17,29. (Worldwide\*)  
1,3,5,7,8,18,19,20,26,28

300 Mbps CAT 6 LTE

Additional regulatory information: PTCRB (US),  
RCM (ANZ, APAC), GCF (EU)

## Supported UICC/SIM

1 \* external SIM card

## Regulatory

FCC (US)

CB (IEC)

CISPR (Australia/New Zealand)

PTCRB (North America)

RCM (Australia/New Zealand, Asia Pacific)

GCF (EU)

## Warranty

Full lifetime hardware warranty with next-day  
advanced replacement included.

## Included in box

MG21 (North America) 1 x MG21-HW-NA	1 x Mounting plate and screw set
--	----------------------------------

MG21 (World wide) 1 x MG21-HW-WW	1 x Mounting plate and screw set
-------------------------------------	----------------------------------

MG21E (North America) 1 x MG21E-HW-NA	1 x Mounting plate and screw set 2 x dipole antennas
--	---

MG21E (World wide) 1 x MG21E-HW-WW	1 x Mounting plate and screw set 2 x dipole antennas
---------------------------------------	---